

COMPACT L-BLOCK WITH DOSE CALIBRATOR SHIELD

The unique Compact L-Block with Dose Calibrator Shield is designed to maximize space in facilities receiving and preparing doses of high-energy nuclides such as FDG F-18. This unit provides convenient access and viewing of the work area and incorporates a built-in calibration chamber shield. The special shield is designed to accommodate a chamber that is through-mounted in a countertop (customer responsible for installation). The chamber shield accommodates all Atomlab chambers and many others (check chamber shield specifications to determine fit). This combination of L-block and dose calibrator shield eliminates the need to purchase interlocking shielding rings. This unit is constructed of lead encased in steel. It features a large 8" x 8" x 4" lead glass window with adjustable window angle, 1.5" thickness lead shielding in front, and 1" thick lead in the base and in the chamber shield. A special plate with a hex-shaped recess is mounted on the L-Block base to facilitate one-handed loading and unloading of dose pigs incorporating hex-shaped bottoms. The optional 042-434 Lead Brick Cave fits neatly into the sides of the vertical section to provide lateral shielding around the full perimeter of the L-block's base. For hot labs in mobile vans, the optional Brick Cave Cover will prevent the cave from shifting when the vehicle is in motion.

SPECIFICATIONS:

042-433 Compact L-Block with Dose Calibrator Shield
Dimensions: 18" w x 21.5" depth x 26" h (45.7 x 54.6 x 66 cm)

Lead Shielding:

Front: 1.5" thick (3.8 cm)

Base: 1" thick (2.5 cm)

Calibrator Shield: 1" thick (2.5 cm)

Calibrator Shield Inside Dimensions: 6.85" I.D. x 10.25" h (17.4 x 26 cm)

Lead Glass Window:

Dimensions: 8" w x 8" h x 4" thick (20.3 x 20.3 x 10.2 cm)

Density: 5.2 g/cm³

Finish: Powder coat

Weight: 570 lb (259 kg)

042-434 Interlocking Lead Brick Cave

Dimensions: (I.D. working area with L-Block Shield)
14" w x 16.32" depth x 13.82" h (35 x 40.8 x 35.6 cm)

Lead Shielding: 2" thick (5 cm)

Finish: Paint

Weight: 597 lb (271 kg)

042-405 Unit Dose Table

Dimensions: 36.75" w x 24" d x 36" h (93.5 x 61 x 91.5 cm)

Weight: 258 lb (117 kg)



FEATURES:

- **1.5" thick lead shielding in front, 1" in base**
- **8" x 8" x 4" adjustable lead glass window**
- **1" thick lead shield surrounds calibration chamber (requires through-counter mounting of chamber)**
- **Optional Lead Brick Cave for complete lateral shielding**

042-433 Compact L-Block with Dose Calibrator Shield, 1.5" lead \$5,795.00
With built-in Dose Calibrator Shield.

Related:

042-434 Lead Brick Cave, 3-wall, 2" lead \$2,700.00
Fits 042-433 L-Block Shield.

042-435 Lead Brick Cave Cover 300.00
Fits 042-434 Lead Brick Cave.

042-405 Table, PET, Unit Dose 2,295.00

Biodex L-Block Shields incorporate a hex-shaped plate to facilitate one-handed loading and unloading of Biodex PET Pigs.

Prices subject to change without notice.

www.jgravengaard.com 2007-07-09

J. Gravengaard Corporation

Medical Imaging Sales & Service

PO Box 20171 Portland, Oregon 97294 Nationwide (800)796-SCAN Local (503)255-0535 Fax (503)255-7047