

TELESCOPING HIGH RANGE SURVEY METER

SPECIFICATIONS:

2000W Telescoping High Range Survey Meter with Dual Energy Compensated Detectors

- **RANGES:** 0-.1, 0-10, 0-100, & 0-100 mR/hr -- 0-1, 0-10, 0-100 & 0-1,000 R/hr
- **PANEL CONTROLS:** OFF, BATTERY CHECK, SPECIAL SCALE EACH RANGE
- **INDICATOR SELECTIONS:**
 - LIGHT AND AUDIBLE OFF
 - LIGHT ON ONLY
 - AUDIBLE ON ONLY
 - LIGHT AND AUDIBLE ON
- **PANEL METER:** 2 1/4" RUGGEDIZED WITH OPTIMIZED ROTATING SCALE FOR EACH RANGE
- **ENERGY RESPONSE:** 63keV to 2 MeV ±15%
- **AUDIO OUTPUT:** HIGH EFFICIENCY PIEZO ELECTRIC - WATER & SOLVENT PROOF
- **POWER SUPPLY:** 2x "D" ALKALINE
- **FINISH:** EPOXY ENAMEL
- **WEIGHT:** 61/2 POUNDS (3 kg) INCLUDING BATTERIES
- **LENGTH:** 36" (91 cm) COLLAPSED - 142" (361 cm) EXTENDED
- **ENVIRONMENTAL:** -20°C (-4°) —60°C (140F°), 5% — 95% RH NON CONDENSING, IPX4
- **METER LIGHT:** LONG LIFE (25,000 HRS) INCANDESCENT WITH SWITCH
- **CONSTRUCTION:** HEAVY DUTY ALUMINUM AND STAINLESS STEEL
- **TELESCOPE:** HEAVY DUTY 10 SECTION STAINLESS STEEL
- **DETECTOR:** DUAL ENERGY COMPENSATED GM OVER 15,000 R/HR SATURATION ON HIGH RANGE
- **CALIBRATION:** INDIVIDUAL ADJUSTMENT EACH RANGE, HV ADJUST AND HV ADJUST CONTROLS

CE Tested. Meets applicable standards.

2000W Telescoping High-range Survey Meter 5,495.00
*Includes survey meter, probe (if required), cable, batteries,
operations and maintenance manual, & calibration certificate*

Prices subject to change without notice.

www.jgravengaard.com 2009-10-08

J. Gravengaard Corporation

Medical Imaging Sales & Service

PO Box 20171 Portland, Oregon 97294 Nationwide (800)796-SCAN Local (503)255-0535 Fax (503)255-7047